

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
31 December 2003 (31.12.2003)

PCT

(10) International Publication Number
WO 2004/000413 A2

(51) International Patent Classification⁷:

A61N

(74) Agents: YOON, Yeo-Pyo et al.; Honesty & Patent, Kuk-dong Bldg. 20F, 60-1, Chungmuro 3-ga, Chung-gu, Seoul 100-705 (KR).

(21) International Application Number:

PCT/KR2003/001220

(22) International Filing Date: 20 June 2003 (20.06.2003)

(25) Filing Language:

Korean

(26) Publication Language:

English

(30) Priority Data:

10-2002-0035305 24 June 2002 (24.06.2002) KR
10-2003-0037632 11 June 2003 (11.06.2003) KR

(71) Applicant and

(72) Inventor: CHUNG, Jong-Pil [KR/KR]; 434, Gunduk 1-ri, Sunjang-myeon Asan-si, Chungcheongnam-do 336-892 (KR).

(72) Inventors; and

(75) Inventors/Applicants (for US only): KANG, Sung-Min [KR/KR]; 116-36, Samsung 2-dong, Kangnam-gu, Seoul 135-873 (KR). KIM, Ye-Won [KR/KR]; 2-206, Seoul Apt, 21, Yeouido-dong, Yeongdeungpo-gu, Seoul 150-875 (KR). LEE, Chong-Hyun [KR/KR]; 103-108, Sinsigaji-Apt, Mok 6-dong, Yangchun-gu, Seoul 158-751 (KR).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished upon receipt of that report

[Continued on next page]

(54) Title: ELECTRIC STIMULATOR FOR ALPHA-WAVE DERIVATION



(57) Abstract: An electric stimulator for alpha-wave derivation is characterized in that frequency selected from a range of 1 Hz to 50 Hz, preferably, 7 Hz to 14 Hz, and an output voltage are applied to auricle of a patient's ears to derive alpha-waves, and that cycle and intensity of stimulation are varied depending upon body temperature and blood sugar. Prompt reaction may be obtained by directly applying the voltage to the ears, and the reaction may continue when stimulation is extended. In addition, it is suitable to treat various diseases having common cause due to stress or arousal reaction in the human body.

BEST AVAILABLE COPY